



PRODUCT CERTIFICATE OF COMPLIANCE

UniLED MK6 HAND RAIL LIGHT

UNIT 6,
ARTHUR DRIVE,
HOO FARM INDUSTRIAL ESTATE,
KIDDERMINSTER,
WORCESTERSHIRE, DY11 7RA

TEL: 01562 66441
FAX: 01562 829992
Website: WWW.plmgroup.co.uk
Email: info@plmgroup.co.uk

PRODUCT TYPE : UL HR MK6 4W - 24

VOLTAGE	24 VDC	IK RATING	10
WATTAGE	4 WATTS	IP RATING	67
UMSUG	TBA	NOM. WEIGHT	300 gr.
LAMP TYPE	SMT LED ARRAY	NOM. SIZE	455mm L X 23mmW X 14mmD
OPERATING TEMP	-20 TO + 60 CENTIGRADE	EFFICACY	> 70 Lm/W

The MK6 UniLED Hand Rail Light is manufactured to comply with the requirements of BS EN 60598-1:2008, which incorporate CENELEC amendment A11, for Class 3 SELV Luminaires, ROHS compliance, and CE marking.

ADDITIONALLY, the MK6 UniLED Hand Rail Light Fitting, when deployed as an Emergency Luminaire, also complies with BS EN 60598-2-22: 1998 + A2:2008 "Particular Requirements - Luminaires for Emergency Lighting".

Lengths shorter than 455mm can be supplied; for example 200mm, 300mm, 450mm, or any bespoke length a project might require.

NB. Deploying the MK6 Hand Rail Light as an emergency luminaire requires that the standard Outdoor Grade cable fitted to the lights be replaced with "FIRETUF" cable or equivalent and that through wiring be accomplished via ceramic terminal blocks since the lights would be connected to a centralised back up battery system.



Julian Ding, AILE
Technical Director
PLM Illumination Limited


January 2013

RoHS Compliant
Directive 2005/95/EC

